



Hot Water 210

Thin cover



Application

Extremely flexible, high pressure hose for cleaners. Suitable for passage of water, water-soap, emulsion. Safety factor 1:4 (according to IEC 335-2)

	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/m	lbs/ft
210T-06-04	06	-4	6,4	1/4"	12,8	0.50	210	3100	840	12400	100	3.94	0,21	0.14
210T-08-05	08	-5	7,9	5/16"	14,4	0.57	210	3100	840	12400	110	4.33	0,26	0.18
210T-10-06	10	-6	9,5	3/8"	16,9	0.67	210	3100	840	12400	120	4.72	0,32	0.22
210T-12-08	12	-8	12,7	1/2"	19,9	0.78	180	2600	720	10400	160	6.30	0,40	0.27
210T-16-10	16	-10	15,9	5/8"	23,1	0.91	130	1900	520	7600	200	7.87	0,46	0.31

Construction:
Tube: Black synthetic rubber
Reinforcement: One high tensile steel braid
Cover: Black or blue, synthetic rubber resistant to abrasion and weather condition

Temperature:
 -40°C to 150°C
 -40°F to 302°F