



Hot Water 250

Thin cover



Application

High pressure hose for cleaners. Suitable for passage of water, water-soap, emulsion.
Safety factor 1:4 (according to IEC 335-2)

	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/m	lbs/ft
250T-06-04	06	-4	6,4	1/4"	12,8	0.50	250	3650	1000	14600	100	3.94	0,21	0.14
250T-08-05	08	-5	7,9	5/16"	14,4	0.57	250	3650	1000	14600	110	4.33	0,26	0.18
250T-10-06	10	-6	9,5	3/8"	16,9	0.67	250	3650	1000	14600	120	4.72	0,32	0.22
250T-12-08	12	-8	12,7	1/2"	19,9	0.78	210	3100	840	12400	160	6.30	0,40	0.27

Tube: Black synthetic rubber
Reinforcement: One high tensile steel braid
Cover: Black or blue, synthetic rubber resistant to abrasion and weather condition

Temperature:
 -40°C to 150°C
 -40°F to 302°F

DIESE RUBBER HOSES S.p.A.

Via Provinciale, 8 – SP 155 - 24040 - FILAGO (Bergamo) ITALY
 Phone: +39 (035) 49.42.300
 e-mail: diesse@diesserubber.com
www.diesserubber.com