



# Hot Water 400 Compact



## Application

High pressure, compact hose for cleaners. Suitable for passage of water, water-soap, emulsion. Safety factor 1:4 (according to IEC 335-2)

	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/m	lbs/ft
400K-06-04	06	-4	6,4	1/4"	13,3	0.52	400	5800	1600	23200	60	2.36	0,27	0.18
400K-08-05	08	-5	7,9	5/16"	15,2	0.60	400	5800	1600	23200	70	2.76	0,34	0.23
400K-10-06	10	-6	9,5	3/8"	17,0	0.66	400	5800	1600	23200	80	3.15	0,40	0.27
400K-12-08	12	-8	12,7	1/2"	20,9	0.82	300	4350	1200	17400	100	3.94	0,54	0.36

**Construction:**  
**Tube:** Black synthetic rubber  
**Reinforcement:** Two high tensile steel braids  
**Cover:** Black or blue, synthetic rubber resistant to abrasion and weather condition

**Temperature:**  
 -40°C to 150°C  
 -40°F to 302°F