



# Hot Water 400 Thin cover



## Application

High pressure, compact hose for cleaners. Suitable for passage of water, water-soap, emulsion. Safety factor 1:4 (according to IEC 335-2)

	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/m	lbs/ft
400T-06-04	06	-4	6,4	1/4"	14,6	0.57	400	5800	1600	23200	100	3.94	0,37	0.25
400T-08-05	08	-5	7,9	5/16"	16,1	0.63	400	5800	1600	23200	110	4.33	0,42	0.28
400T-10-06	10	-6	9,5	3/8"	18,6	0.73	400	5800	1600	23200	120	4.72	0,53	0.36
400T-12-08	12	-8	12,7	1/2"	21,4	0.84	300	4350	1200	17400	160	6.30	0,61	0.41

**Construction:**  
**Tube:** Black synthetic rubber  
**Reinforcement:** Two high tensile steel braids  
**Cover:** Black or blue, synthetic rubber resistant to abrasion and weather condition

**Temperature:**  
 -40°C to 150°C  
 -40°F to 302°F