









Jack hose



Application

Hydraulic jack applications with petroleum and water-base fluids. Meets the performance requirements of the Material Handling Institute Specification IJ100. 10,000PSI Static Pressure Only. Suitable for passage of mineral and vegetable oils, water-based solutions, water air and inert gases.

														
	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/m	lbs/ft
JCK-06-04	06	-4	6,4	1/4"	13,3	0.52	700	10000	1400	20000	50	1.97	0,34	0.23
JCK-10-06	10	-6	9,5	3/8"	17,3	0.68	700	10000	1400	20000	65	2.56	0,42	0.28

Construction:
Tube: Black synthetic rubber resistant to oils
Reinforcement: Two high tensile steel braids
Cover: Black, synthetic rubber resistant to oils, abrasion and weather condition

Temperature:
 -40°C to 100°C (125°C discontinuous)
 -40°F to 212°F (257°F discontinuous)

Version available:
 MSHA COVER
 MSHA HARC COVER
 MSHA ENDLESS COVER
 HARC COVER
 ENDLESS COVER