



Push-on



Application

Low pressure hose for hydraulic applications Suitable for passage of mineral and vegetable oils, water-based solutions, water air and inert gases. Push-On hose can be used with Push-On fittings but is not recommend in vibrating or critical application.

	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/m	lbs/ft
PUSHON-06-04	06	-4	6,4	1/4"	12,5	0.49	21	304	84	1216	75	3.00	0,11	0.07
PUSHON-10-06	10	-6	9,5	3/8"	15,6	0.61	21	304	84	1216	75	3.00	0,15	0.10
PUSHON-12-08	12	-8	12,7	1/2"	19,1	0.75	21	304	84	1216	125	5.00	0,22	0.14
PUSHON-16-10	16	-10	15,9	5/8"	22,6	0.89	21	304	84	1216	150	6.00	0,26	0.17
PUSHON-19-12	19	-12	19,0	3/4"	26,1	1.03	21	304	84	1216	175	7.00	0,31	0.20
PUSHON-25-16	25	-16	25,4	1"	33	1.30	21	304	84	1216	200	8.00	0,44	0.29

Construction:

Tube: Black synthetic rubber resistant to oils
Reinforcement: One high resistant textile braid
Cover: Black, synthetic rubber resistant to oils, abrasion and weather condition

Temperature:

-40°C to 100°C (125°C discontinuous)
 -40°F to 212°F (257°F discontinuous)

Version available:

MSHA COVER
 MSHA HARC COVER
Color available:
 Black, Red