



Push-on Fuel



Application

Low pressure hose for hydraulic applications Suitable for passage of mineral and vegetable oils, water-based solutions, water air and inert gases. Push-On hose can be used with Push-On fittings but is not recommended for vibrating or critical application. Compatible with gasoline, diesel and biodiesel. Meets SAE 30R2 SAE 30R6 and SAE 30R7 requirements.

	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/m	lbs/ft
PUSHON-06-04-FL	06	-4	6,4	1/4"	12,5	0.49	21	304	84	1216	75	3.00	0,11	0.07
PUSHON-10-06-FL	10	-6	9,5	3/8"	15,6	0.61	21	304	84	1216	75	3.00	0,15	0.10
PUSHON-12-08-FL	12	-8	12,7	1/2"	19,1	0.75	21	304	84	1216	125	5.00	0,22	0.14
PUSHON-16-10-FL	16	-10	15,9	5/8"	22,6	0.89	21	304	84	1216	150	6.00	0,26	0.17
PUSHON-19-12-FL	19	-12	19,0	3/4"	26,1	1.03	21	304	84	1216	175	7.00	0,31	0.20
PUSHON-25-16-FL	25	-16	25,4	1"	33	1.30	21	304	84	1216	200	8.00	0,44	0.29

Construction:
Tube: Black synthetic rubber resistant to oils
Reinforcement: One high resistant fiber braid
Cover: Black, synthetic rubber resistant to oils, abrasion and weather condition

Temperature:
 -40°C to 100°C (125°C discontinuous)
 -40°F to 212°F (257°F discontinuous)

Version available:
 MSHA COVER
Color available:
 Black