



Waterblast 1380 Bar

20000PSI



Application

Very high constant pressure hose for water descaling system. Suitable for passage of water, water-soap, emulsion.

Safety factor 1:2,5

	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/m	lbs/ft
WB1380-06-04	6	-04	6.4	1/4"	17,8	0.70	1380	20000	3450	50000	125	4.92	0,73	0.49
WB1380-10-06	10	-06	9.5	3/8"	21,5	0.85	1380	20000	3450	50000	150	5.91	1,05	0.71
WB1380-12-08	12	-08	12.7	1/2"	28,8	1.13	1450	21000	3625	52500	250	9.84	1,87	1.26
WB1380-19-12	19	-12	19.0	3/4"	36,2	1.43	1350	19600	3375	49000	280	11.02	2,65	1.78

Construction:

Tube: Black synthetic rubber

Reinforcement: Four high tensile steel spirals up to -6, six spirals -8 and -12

Cover: Black, synthetic rubber resistant to oils, abrasion and weather condition

Temperature:

-40°C to +90°C Operating Temperature Range

-10°C to +80°C Continuous Service Temperature Range

-40°F to 194°F Operating Temperature Range

+14°F to 176°F Continuous Service Temperature Range