



# Waterblast 700 Bar

10000PSI



## Application

Very high constant pressure hose for water descaling system. High abrasion resistant cover  
Suitable for passage of water, water-soap, emulsion.  
Safety factor 1:2,5

	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/m	lbs/ft
WB700-06-04	6	-04	6.4	1/4"	16,9	0.67	700	10000	1750	25000	125	4.92	0,61	0.41
WB700-10-06	10	-06	9.5	3/8"	20,3	0.80	700	10000	1750	25000	180	7.09	0,75	0.50
WB700-12-08	12	-08	12.7	1/2"	23,2	0.91	700	10000	1750	25000	220	8.61	0,94	0.63
WB700-19-12	19	-12	19.0	3/4"	31,4	1.24	700	10000	1750	25000	280	11.02	1,63	1.10
WB700-25-16	25	-16	25.4	1"	38,1	1.50	700	10000	1750	25000	350	14.00	2,18	1.46

**Construction:**  
**Tube:** Black synthetic rubber  
**Reinforcement:** Four high tensile steel spirals  
**Cover:** Black, synthetic rubber resistant to oils, abrasion and weather condition

**Temperature:**  
 -40°C to +90°C Operating Temperature Range  
 -10°C to +80°C Continuous Service Temperature Range  
 -40°F to 194°F Operating Temperature Range  
 +14°F to 176°F Continuous Service Temperature Range