



Waterblast 850 Bar

12000PSI



Application

Very high constant pressure hose for water descaling system. Suitable for passage of water, water-soap, emulsion.

Safety factor 1:2,5

	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/m	lbs/ft
WB850-06-04	6	-04	6.4	1/4"	17,1	0.67	850	12000	2125	30000	125	4.92	0,61	0.41
WB850-10-06	10	-06	9.5	3/8"	20,5	0.81	850	12000	2125	30000	150	5.91	0,84	0.56
WB850-12-08	12	-08	12.7	1/2"	24,1	0.95	850	12000	2125	30000	260	10.50	0,97	0.65
WB850-19-12	19	-12	19.0	3/4"	31,7	1.25	850	12000	2125	30000	280	11.02	1,70	1.14
WB850-25-16	25	-16	25.4	1"	38,6	1.52	850	12000	2125	30000	355	13.98	2,26	1.52

Construction:
Tube: Black synthetic rubber
Reinforcement: Four high tensile steel spirals
Cover: Black, synthetic rubber resistant to oils, abrasion and weather condition

Temperature:
 -40°C to +90°C Operating Temperature Range
 -10°C to +80°C Continuous Service Temperature Range
 -40°F to 194°F Operating Temperature Range
 +14°F to 176°F Continuous Service Temperature Range