



Water Wave

STEAM CLEANING SERVICE UP TO 163°C (325°F)



	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	Kg/m	lbs/ft
DSWW-10-06	10	-6	9,5	3/8"	17,4	0.69	25	350	180	7.09	0,19	0.13
DSWW-12-08	12	-8	12,7	1/2"	21	0.83	25	350	270	10.63	0,38	0.26

PRESSURE WASHER SERVICE UP TO 121°C (250°F)

Application

For use on either steam cleaner machines or combination steam cleaner/pressure washer machines.

	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	Kg/m	lbs/ft
DSWW-10-06	10	-6	9,5	3/8"	17,4	0.69	210	3000	180	7.09	0,19	0,13
DSWW-12-08	12	-8	12,7	1/2"	21	0.83	170	2500	270	10.63	0,38	0,26

Applications: For use on either steam cleaner machines or combination steam cleaner/pressure washer machines.

Construction:
Tube: Synthetic rubber
Reinforcement: One high tensile steel braid
Cover: Synthetic black cover