

## Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

This certificate is issued to:

<b>PRODUCER</b>	Diesse Rubber Hoses SpA
<b>PLACE OF PRODUCTION</b>	Via Provinciale, 8 24040 Filago (BG) Italy
<b>DESCRIPTION</b>	Fire safe flexible hoses made up of synthetic rubber with one or two high tensile braid reinforcement, or four or six spirals, with end fittings.
<b>TYPE</b>	DS 13, DS-4SH, DS-4SP, DS1-T.1SN, DS2-T.2SN, DS1-SC and DS2-SC
<b>APPLICATION</b>	Marine, offshore and industrial use, including the following marine uses; Steering gear systems; Lube and fuel oil systems; Sea water systems; Fresh water systems; Sanitary systems.
<b>SPECIFIED STANDARDS</b>	Lloyd's Register's Rules and Regulations for the Classification of Ships; BS EN 853:1997; BS EN 856:1997; BS EN 857:1997;
<b>RATINGS</b>	<b>DS-13</b> Nominal diameter (mm): 19 to 51 Working pressure (bar): 345 Reinforcement: 4 spirals up to 25mm ND 6 spirals over 31mm ND
<b>Certificate No.</b>	07/00017
<b>Issue Date</b>	05 March 2007
<b>Expiry Date</b>	04 March 2012
<b>Sheet</b>	1 of 3



P.F. Moysey  
London Design Support Services  
Lloyd's Register EMEA

Lloyd's Register EMEA  
71 Fenchurch Street, London EC3M 4BS

## RATINGS (continued)

### DS-4SH

Nominal diameter (mm): 19 to 51  
Working pressure (bar): 450 to 250  
Reinforcement: 4 spirals

### DS-4SP

Nominal diameter (mm): 19 to 51  
Working pressure (bar): 500 to 165  
Reinforcement: 4 spirals

### DS1-T.1SN

Nominal diameter (mm): 6 to 51  
Working pressure (bar): 225 to 40  
Reinforcement: 1 braid

### DS2-T.2SN

Nominal diameter (mm): 6 to 51  
Working pressure (bar): 275 to 100  
Reinforcement: 2 braids

### DS1-SC

Nominal diameter (mm): 6 to 25  
Working pressure (bar): 275 to 100  
Reinforcement: 1 braid

### DS2-SC

Nominal diameter (mm): 6 to 25  
Working pressure (bar): 420 to 185  
Reinforcement: 2 braids

## OTHER CONDITIONS

1. The hoses are to be installed in accordance with the manufacturer's recommendations and instructions.
2. The manufacturer's recommendations on replacement of the hoses after a specified period in service is to be strictly observed.

Certificate No. 07/00017  
Issue Date 05 March 2007  
Expiry Date 04 March 2012  
Sheet 2 of 3



P.F. Moysey  
London Design Support Services  
Lloyd's Register EMEA

Lloyd's Register EMEA  
71 Fenchurch Street, London EC3M 4BS

*"This Certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid certificate."*

*The Design Appraisal Document No. 07/00017 and its supplementary Type Approval Terms and Conditions form part of this Certificate.*

<b>Certificate No.</b>	07/00017
<b>Issue Date</b>	05 March 2007
<b>Expiry Date</b>	04 March 2012
<b>Sheet</b>	3 of 3



P.F. Moysey  
London Design Support Services  
Lloyd's Register EMEA

Lloyd's Register EMEA  
71 Fenchurch Street, London EC3M 4BS

Lloyd's Register, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register Group'. The Lloyd's Register Group assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register Group entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.